

ARADA
— DEVON —

Manufacturer: Arada Ltd, The Fireworks, Weycroft Avenue, Axminster, Devon, United Kingdom EX13 5HU

Range Designation: Ecoburn

Intended Use: Free Standing Domestic Heating Appliance

Independent Performance and Safety tested: UKCA - Kiwa Gastec, Approved Body No. 0558

CE - Kiwa Cermet Italia S.p.A, Notified Body No. 0476

Constancy of Performance System AVCP: System 3

Model	Ecoburn 5 (S3)	Ecoburn 5 Widescreen (S3)	Ecoburn 7 (S3)
Approximate Output Range: (kW)	1.5 - 7	1.5 - 7	1.5 - 10
Harmonised EN European Standard (hEN):	EN13240: 2001 Amd 2:2004	EN13240: 2001 Amd 2:2004	EN13240: 2001 Amd 2:2004
Additional Characteristics Test Standard:	DIN +	DIN +	DIN +
Additional Particulate Emission Test Standard:	PD6434	PD6434	PD6434
Test Report reference:	61133	61136-1	61136-2
Performance Characteristics on Wood Fuel			
Total Efficiency: (%)	79.8	81.3	78.2
Declared nominal output: (kW)	4.9	4.9	7
Tested nominal Output: (kW)	4.9	4.9	7.1
Flue gas mass flow: (g/s)	4.7	4.1	5.6
Mean CO emission (@13% O ₂) : (%)	0.11	0.1	0.09
Mean OGC emission (@13% O ₂): (Nm _g /m ₃)	86	68	72
Mean NO _x emission (@13% O ₂): (Nm _g /m ₃)	95	82	102
DIN+ particulates (@13% O ₂): (Nm _g /m ₃)	27	22	38
PD6434 Particulate Emissions High output: (gh-1)	2.7	2.1	4.9
PD6434 Particulate Emissions Low output: (gh-1)	2	1.1	2.8
Mean Flue Temperature: (Deg C)	255	257	310
Underhearth Temperature: (Deg C)	51.2	46.4	95
Approximate Max Log Length: (mm)	300	375	375
Performance Characteristics on Maxibrite Briquetted Smokeless Fuel			
Total Efficiency: (%)	82.3	79.3	81.2
Declared nominal output: (kW)	4.9	4.9	7
Tested nominal output: (kW)	4.9	4.9	7.1
Flue gas mass flow: (g/s)	3.5	4.2	5.6
Mean CO emission (@13% O ₂) : (%)	0.1	0.09	0.11
Mean OGC emission (@13% O ₂): (Nm _g /m ₃)	26	19	39
Mean NO _x emission (@13% O ₂): (Nm _g /m ₃)	94	102	116
DIN+ particulates (@13% O ₂): (Nm _g /m ₃)	10	9	10
Mean Flue Temperature: (Deg C)	254	281	271
Underhearth Temperature: (Deg C)	51.2	46.4	95
Safet Distances From Combustibles (standard flue connection)			
Side Wall: (mm)	550	450	600
Rear Wall: (mm)	700	650	650
Safety Distances From Combustibles (Schiedel Twin wall Insulated Flue)			
Side Wall: (mm)	500	250	500
Rear Wall: (mm)	75	50	100

The performance of the product identified above is in conformity with the set of declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under sole responsibility of the manufacturer identified above.

Signed On Behalf Of Manufacturer:

ARADA
— DEVON —

J. Stantford

18 February 2025