Diverter Valve

Diverter Valve

Allows one pump to draw from two locations

- Robust, reliable design
- Teflon® lubricated non-stick operation
- Precision machined for odour-proof seal
- Withstands sewage/black waste, saltwater and bilgewater
- Models available in either 25 mm (1") or 38 mm (1 $^{1}/_{2}$ ") hose connection

Typical Uses

- Suitable for electric or manual waste management systems
- Used in bilge and toilet waste systems
- Diverts flow to holding tank or overboard or deck pump out

Model Specifications

Model	Diverter Valve	Diverter Valve
Product Code	DV5630	DV5606
Hose Connections	25 mm (1")	38 mm (1½")
Materials	Main Body: Acetal, Teflon®, Handle: PTFE Polyester	


Allows one pump to draw from two locations

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support.



Diverter Valve 5 Year Warranty



Bilge Strainers/Strum Boxes

Strainer


³/₄" (19mm) Strainer with Multi-Directional Port and Non-Return Valve



SB3422 (Top/Side entry)

120mm

Front View





Front View

Strainer

Front View

1" (25mm) / 1 1/2" (38mm) Strainers available with top or side entry



