



Product Data Sheet  
Version 02/ 2012  
Translation

## Sika® Teak Oil Neutral

Protective oil for teak boat decks

### Properties

Chemical base	Natural oil, solvent free
Colour	Colourless
Density	0,9
Viscosity	Liquid
Flash point	>150°C
Application method	Apply with brush, roll or by spraying
Consumption	11 to 140 g/m <sup>2</sup> (depending on wood type; quality and dryness)
Storage conditions	Store in dry conditions

*Consult safety data sheet for complete storage instructions*

### Description

Sika® Teak Oil Neutral is a protective coating for teak decks based on vegetal oils.

### Advantages

- Based on vegetal oils
- Easy and quick application
- Compatible with Sikaflex® Marine product range
- Provides high UV protection

### Application field

Sika® Teak Oil Neutral is used to protect the teak decks of sailboats and yachts

It protects the wood, makes it resistant and restores its natural look.

Sika® Teak Oil Neutral is a long-term protection against sea water, freshwater, UV and other climatic factors

This product is intended only for experienced applicators.

Tests on substrates under real conditions must be performed to check the compatibility of the product

### Characteristics

The combination of high-quality vegetable oils with different viscosities lead to a good penetration into the wood and a quick drying time through the content in natural drying agents.

### Documents

The following documents are available on demand:

- Product safety data sheet.

### Packaging

Bottle	500 ml
Can	2,5 l

### Value base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### Important information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet.

### Legal note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Industry

