



SIS 440 Teak Deck Caulking Yield

Use this chart to determine how much caulk is required for your project. The numbers in bold indicate the linear feet yield per 10.3 oz (305ml) Cartridge based on the seam width and depth.

Linear Feet Yield per 10.3 fl.oz. Cartridge*

			Seam Depth									
			1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"
			0.125"	0.1875"	0.25"	0.3125"	0.375"	0.4375"	0.5"	0.5625"	0.625"	0.75"
Seam Width	1/8"	0.125"	69'	46'	35'	28'	23'	20'	17'	15'	14'	12'
	3/16"	0.1875"	46'	31'	23'	19'	15'	13'	12'	10'	9'	8'
	1/4"	0.250"	35'	23'	17'	14'	12'	10'	9'	8'	7'	6'
	5/16"	0.3125"	28'	19'	14'	11'	9'	8'	7'	6'	6'	5'
	3/8"	0.375"	23'	15'	12'	9'	8'	7'	6'	5'	5'	4'
	7/16"	0.4375"	20'	13'	10'	8'	7'	6'	5'	4'	4'	3'
	1/2"	0.500"	17'	12'	9'	7'	6'	5'	4'	4'	3'	3'

* Double the yield for SIS 440 Foil Packaging (20 oz)

Linear Meter Yield per 305 ml E Cartridge*

			Seam Depth									
			3mm	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm
Seam Width	3mm	24m	18m	14m	12m	10m	9m	8m	7m	6m	6m	5m
	4mm	18m	13m	11m	9m	8m	7m	6m	5m	5m	4m	4m
	5mm	15m	11m	9m	7m	6m	5m	5m	4m	4m	4m	3m
	6mm	12m	9m	7m	6m	5m	5m	4m	4m	3m	3m	3m
	7mm	10m	8m	6m	5m	4m	4m	3m	3m	3m	2m	2m
	8mm	9m	7m	5m	5m	4m	3m	3m	3m	2m	2m	2m
	9mm	8m	6m	5m	4m	3m	3m	3m	2m	2m	2m	2m
	10mm	7m	5m	4m	4m	3m	3m	2m	2m	2m	2m	2m
	11mm	6m	5m	4m	3m	3m	3m	2m	2m	2m	2m	1m
	12mm	6m	4m	4m	3m	3m	2m	2m	2m	2m	1m	1m
13mm	5m	4m	3m	3m	2m	2m	2m	2m	1m	1m	1m	

* Double the yield for SIS 440 Foil Packaging (592 ml)

Note: Linear feet and meter quantities are estimates and will vary by the user's technique.

Waste Factor in Calculation: 25%

QUESTIONS

Telephone: 941-756-0600, press "1" for Products

Email: products@teakdecking.com



Teakdecking Systems
"The Professional's Choice"

Teakdecking Systems, 7061 15th Street East, Sarasota, FL 34243